

Date: _____

For: File Resubmit
 Approval Other _____

PO No.: _____

Architect: _____

GC: _____

Engr: _____

Mech: _____

Rep: _____

(Company) _____

(Project Manager) _____



Packaged Terminal Air Conditioners (PTAC) 208-230V Heat Pump Models



Model	Cooling Capacity (Btu/h)	EER	Heating Capacity (Btu/h)	COP	Net Weight (lbs)	Sound Pressure IDU/ODU	Air Circulation H/L (CFM)	Dehumidification (pts/hr)	Power Supply (V/Hz/Ph)	Rated Amps (A) (Cooling)	Rated Amps (A) (Heating)	Cooling Power Input (W)	Heating Power Input (W)
LP073HDUC	7,100/7,300	13.3	6,200/6,400	3.6	95	45/61	270/225	1.7	208-230/60/1	2.7/2.5	2.6/2.4	535/550	500/520
LP093HDUC	9,300/9,500	12.9	8,000/8,200	3.6	106	46/61	270/225	2.6	208-230/60/1	3.6/3.3	3.3/3.0	720/735	655/670
LP123HDUC	12,000/12,200	11.9	10,600/10,800	3.5	106	50/63	420/353	3.0	208-230/60/1	5.2/4.8	4.6/4.3	1,010/1,025	885/905
LP153HDUC	14,900/15,100	11.2	13,200/13,400	3.1	115	51/64	420/353	4.3	208-230/60/1	6.6/6.1	6.2/5.7	1,330/1,345	1,250/1,265

Standard Features:

- Auto restart
- Digital control display
- Dip switch setting for temperature limiting
- Energy saver mode
- Freeze room protection
- Front desk control
- GoldFin™ anti-corrosion treatment for condenser
- High energy efficiency
- Temperature display on unit
- Ultra-quiet operation
- Positive Temperature Coefficient (PTC) Heater

Optional Accessories:

- Wall Sleeve - 42"W x 16"H x 13-3/4"D (AYSVB01A)
- Condensate Drain Kit (AYDR101A)
- Replacement Filter 10 Pack (AYFT110)
- Leveling Legs (AYLL101A)

Architecture Grille:

- Aluminum (AYAGALA01A)
- Dark Bronze (AYAGALB01A)
- Soft Dove (AYAGALC01A)

Sub Base:

- 208-230V 20A (AYSB1101A)

Optional Wall Thermostats




- Wired Wall Thermostat (PYRCUCA0B)
- Wireless Wall Thermostat (PYRUCC1HB)
- Wired Wall Thermostat Connection Kit (AYWH101)

- 1: EER - Energy Efficiency Ratio
- 2: COP - Coefficient of Performance
- 3: IDU - Indoor Unit
- 4: ODU - Outdoor Unit
- 5: MOP - Maximum Overcurrent Protection
- 6: MCA - Minimum Circuit Ampacity
- 7: Values are 208V / 230V if not specified

Mandatory Accessories:

Select MANDATORY accessory power cord by heating capacity required and/or circuit

POWER CORD	VOLTAGE	HEATER WATTS	HEATER CURRENT	MOP	MCA	HEATING CAPACITY (Btu/h)
<input type="checkbox"/> AYUH2115	208/230	2,300/2,400 W	11.2/10.5 A	15 A	14.5 A	7,800/8,100
<input type="checkbox"/> AYUH2120	208/230	3,200/3,300 W	15.5/14.5 A	20 A	19.8 A	10,900/11,200
<input type="checkbox"/> AYUH2130	208/230	4,600/4,700 W	22.3/20.6 A	30 A	28.3 A	15,700/16,000

Power Cord	Use Wall Receptacle	Power Supply
AYUH2115	 Standard 208/230V, grounding receptacle rated 15A	Use 15 AMP. time delay fuse or 15 AMP. Circuit breaker.
AYUH2120	 Standard 208/230V, grounding receptacle rated 20A	Use 20 AMP. time delay fuse or 20 AMP. Circuit breaker.
AYUH2130	 Standard 208/230V, grounding receptacle rated 30A	Use 30 AMP. time delay fuse or 30 AMP. Circuit breaker.